



# LITEPLAST Wood

DATA SHEET  
06/2019



## DESCRIPTION:

Acrylic lightweight filler, ready to use, easy to apply.

## APPLICATIONS:

LITEPLAST WOOD is specially recommended to repair and fill cracks, holes, fissures, etc., in wooden pieces and boards.

It can be sanded, painted and varnished after drying.

## PROPERTIES:

LITEPLAST WOOD dries very fast. It does not shrink, nor crack in any thickness applied.

## INSTRUCTIONS OF USE:

The surfaces must be clean and free from dust and grease.

Apply LITEPLAST WOOD with a flexible spatula on the surface to be filled wetting it a little in order to promote the adhesion and smooth the surface with a wet spatula to the desired shape. Once the product is dry, at least 2 hours depending on the thickness applied, it can be sanded if necessary. After dry, LITEPLAST WOOD can be painted or varnished using common acrylic or polyurethane varnishes in the market.

## TECHNICAL FEATURES:

**Appearance:** Wood-coloured paste.

**Density:**  $0,450 \pm 0,010 \text{ gr/cm}^3$

**Viscosity:** Paste of thixotropic consistency.

## STORAGE:

At least 24 months in closed containers at a recommended temperature between 5 to 30°C.

## CLEANING:

The tools can be cleaned with warm water while the product is still fresh.

## PRESENTATION:

Tube 150 ml.

Jar 250 ml

## HEALTH & SAFETY:

According to actual legislation, this product is risk free and does not require and special safety measure during handling or storage.

*For more information request Safety Data Sheet*

"The information contained herein is offered in good faith based on Selena's research and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information shall not be used in substitution for customer's tests to ensure that Selena's products are fully satisfactory for your specific applications. Selena's sole warranty is that the product will meet its current sales specifications. Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted. Selena FM S.A. specifically disclaims any other expressed or implied warranty of fitness for a particular purpose or merchantability. Selena disclaims liability for any incidental or consequential damages. Suggestions of use shall not be taken as inducements to infringe any patent. Technical indications and data appearing in this brochure are based on our current knowledge and experience and we decline all responsibility for consequences derived from inadequate use. Therefore, our guarantee is limited exclusively to the quality of the product supplied. This technical information can be modified without notice. If necessary request it periodically."



Quilosa - Selena Iberia S.L.U.

Centro empresarial Rivas Futura, C/ Marie Curie 19, Planta 6.1, 28521 Rivas, Madrid, Spain,  
Tel: +34 902 02 18 02 – Fax: +34 914 999 796, [info@quilosa.es](mailto:info@quilosa.es), [www.quilosa.com](http://www.quilosa.com)