



# BRICOFIX

## Vinyl Wallpaper

DATA SHEET  
06/2019



### DESCRIPTION:

---

Polyvinyl acetate aqueous dispersion based adhesive.

### APPLICATIONS:

---

Specially formulated for pasting wallpaper, both simple and duplex or vinyl.

### PROPERTIES:

---

Forms a transparent elastic film.

### INSTRUCTIONS:

---

Walls must be consistent, clean, dry and grease-free.

The adhesive is applied on the wall using a roller, spatula or brush and may be diluted with up to 15% water.

In cases of very absorbent or poor quality walls, a primer coating should be applied using the product diluted with 50% water.

Hang wallpaper immediately after applying **BRICOFIX VINYL WALLPAPER**, applying even pressure across the entire surface in order to prevent the appearance of creases and air pockets.

### STORAGE:

---

Store for 12 months in tightly sealed original packaging in a cool and dry place.

Protect from frosts.

After long storage periods, stir well before use.

### PRESENTATION:

---

Jar	1 L
Cube	5 L

### TECHNICAL FEATURES

---

Appearance:	Thick liquid with characteristic odour.
pH:	5 ± 0.5
Viscosity:	Brookfield RVT. Sp 7 at 20 rpm, 23°C 60.000 ± 10.000 mPa.s
Minimum temperature for film formation:	5 – 7°C
Open time:	Maximum 10 minutes(undiluted)

### CLEANING:

---

Tools should be cleaned with water immediately after use.

### HEALTH & SAFETY:

---

According to existing legislation, this product is not subject to any special indications regarding risks or safety during use or storage.

*For more information, please request the product safety sheet.*

"The information contained herein is offered in good faith based on Selena's research and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information shall not be used in substitution for customer's tests to ensure that Selena's products are fully satisfactory for your specific applications. Selena's sole warranty is that the product will meet its current sales specifications. Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted. Selena FM S.A. specifically disclaims any other expressed or implied warranty of fitness for a particular purpose or merchantability. Selena disclaims liability for any incidental or consequential damages. Suggestions of use shall not be taken as inducements to infringe any patent.

Technical indications and data appearing in this brochure are based on our current knowledge and experience and we decline all responsibility for consequences derived from inadequate use. Therefore, our guarantee is limited exclusively to the quality of the product supplied. This technical information can be modified without notice. If necessary request it periodically."



Quilosa - Selena Iberia S.L.U.

Centro empresarial Rivas Futura, C/ Marie Curie 19, Planta 6.1, 28521 Rivas, Madrid, Spain,  
Tel: +34 902 02 18 02 – Fax: +34 914 999 796, [info@quilosa.es](mailto:info@quilosa.es), [www.quilosa.com](http://www.quilosa.com)